

## Upínací kuželová pouzdra TLB

Číslo vložky	vrtání pro hřídel	Drážka P9	Délka vložky	Největší průměr kuželu
<b>1008</b>	10	3	22,3	35,0
	11 12	4		
	14 16	5		
	18 19 20 22	6		
	24 25	8*		
<b>1108</b>	10	3	22,3	38,0
	11 12	4		
	14 16	5		
	18 19 20 22	6		
	24 25	8		
	28	8*		
<b>1210</b>	11 12	4	25,4	47,5
	14 16	5		
	18 19 20 22	6		
	24 25 28	8		
	30 32	10		
<b>1310</b>	14 16	5	25,4	51,0
	18 19 20 22	6		
	24 25 28 30	8		
	32 35	10*		
<b>1610</b>	14 15 16	5	25,4	57,0
	18 19 20 22	6		
	24 25 28 30	8		
	32 35 38	10		
	40 42	12		
<b>1615</b>	14 16	5	38,1	57,0
	18 19 20 22	6		
	24 25 28 30	8		
	32 35 38	10		
<b>2012</b>	14 16	5	31,8	70,0
	18 19 20 22	6		
	24 25 28 30	8		
	32 35 38	10		
	40 42	12		
<b>2517</b>	16	5	44,5	85,5
	18 19 20 22	6		
	24 25 28 30	8		
	32 35 38	10		
	40 42	12		
	45 48 50	14		
	55	16		
60	18			
<b>3020</b>	25 28 30	8	50,8	108,0
	32 35 38	10		
	40 42	12		
	45 48 50	14		
	55	16		
	60 65	18		
<b>3030</b>	35 38	10	76,2	108,0
	40 42	12		
	45 48 50	14		
	55	16		
	60 65	18		
70 75	20			
Číslo vložky	vrtání pro hřídel	Drážka P9	Délka vložky	Největší průměr kuželu
<b>3525</b>	35 38	10	64,0	127
	40 42	12		
	45 48 50	14		
	55	16		
	60 65	18		
	70 75	20		
	80 85	22		
	90 95	25		
	100	28*		
<b>3535</b>	35 38	10	88,9	127
	40 42	12		
	45 48 50	14		
	55	16		
	60 65	18		
	70 75	20		
	80 85	22		
	90	25		
<b>4030</b>	40 42	12	76,0	146
	45 48 50	14		
	55	16		
	60 65	18		
	70 75	20		
	80 85	22		
	90 95	25		
100 105 110	28			
115	32*			
<b>4040</b>	40 42	12	101,6	146
	45 48 50	14		
	55	16		
	60 65	18		
	70 75	20		
	80 85	22		
<b>4535</b>	55	16	89,0	162
	60 65	18		
	70 75	20		
	80 85	22		
	90 95	25		
	100 105 110	28		
115 120 125	32			
<b>4545</b>	55	16	114,3	162
	60 65	18		
	70 75	20		
	80 85	22		
	90 95	25		
100 105 110	28			
<b>5040</b>	70 75	20	102,0	178
	80 85	22		
	90 95	25		
	100 105 110	28		
	115 120 125	32		
<b>5050</b>	70 75	20	127,0	178
	80 85	22		
	90 95	25		
	100 105 110	28		
	115 120 125	32		